



Section 3: Pumps

General Information • Grease Pumps • Oil Pumps • Chemical and Material Handling Pumps
Undercoating Pumps

Pneumatic RAM Pumps (Portable)

Alemite Mobile RAM Grease Pumps offer portability, quiet operation and quick serviceability. Most models come equipped with all necessary accessories for fast and easy setup.



FEATURES:

- Air inlet: 1/4 NPTF(f)
- Material outlet: 3/8 NPTF(f)
- Air motor diameter: "3
- Model 9911-A1 comes equipped with a 70-lb. container that can also hold 35-lb. containers (ring included for insert of 35-lb. pail)
- 9911-H1 and 9911-HA1 have built-in carrying handle
- 9951 series features a built-in holster to keep the hose and handle off the floor
- Flexible follower works with straight and tapered containers
- **Included Items:** Control Valve (6320-3) 7' Material Hose (317875-7), Z-Swivel (B52752)

REQUIRED ACCESSORIES for 9911-A1 only (see chart below):

- For 70-lb. Container: Follower (338802).213
- For 35-lb. Container: Follower (337665).213

Product #	Description	Bare Pump	Drum Size	Pump Ratio	Delivery	Cover	Dolly	Weight
9911-A1	(Portable)	9911-R1	see note*	50:1	4.5 lb./min	Included: 323496-A4	Included: 393629	68 lb.
9911-H1	(Portable)	9911-1	35 lb.	50:1	4.5 lb./min	Included: 338166	No	29 lb.
9911-Z1	(Portable)	9911-1	35 lb.	50:1	4.5 lb./min	Included: 338166	Included: 338958	50 lb.
9941	(Portable)	9940	120 lb.	70:1	3.25 lb./min	Included: 338371	Included: 316315-5	54 lb.
9951-1	(Portable)	9950-1	120 lb.	50:1	4.5 lb./min	Included: 338371	Included: 316315-5	50 lb.
9951-T1	(Portable)	9950-1	120 lb.	50:1	4.5 lb./min	Included: 338371	Included: 338958	57 lb.
9911-HA1	(Portable; Metric)	N/A	12.5 kg	50:1	2.04 kg/min	Included: 338981	Order separately 338958	31 lb.
9911-HB1	(Portable; Metric)	N/A	20 kg	50:1	2.04 kg/min	Included: 338982	Order separately 338958	37 lb.
9911-HC1	(Portable; Metric)	N/A	50 kg (120 lb.)	50:1	2.04 kg/min	Included: 338983	Order separately 338958	42 lb.

IMPORTANT INFORMATION

* 9911-A1 will hold 70 lb. bulk grease or 35 lb. original refinery pail

NOTE: Delivery based on NLGI #2 at 77°F, 150 psi. Delivery rate may vary based on grease type, temperature, pressure, distance pumped and other conditions.